

POSITIONIT[®] PI 35

New Heavy-Duty Pan and Tilt Positioner by Will-Burt

- Payload Capacity – Up to 35 ft.-lbs. / 47 Nm
- Waterproof – IP 68 Rated
- Pelco-D Communications
- Universal Mounting Plate

PositionIt by Will-Burt is a maintenance-free pan and tilt positioner designed to provide years of trouble-free service. An IP68 rating delivers dust and water protection. The gear box is designed to minimize backlash and provides higher gear ratios for lower speeds along with mechanical braking. Long-life potentiometers are standard with PositionIt.



ESSENTIAL FEATURES

- **Strong lightweight construction**
 - Die-cast aluminum casing
- **Pelco-D RS-485 communication**
- **Minimal backlash**
 - Precision turned and milled components with ball races on major axes
- **Absolute positioning**
- **Built to last**
 - Stainless steel fasteners
- **Weatherproof**
 - IP 68 rating
- **Simple to install**
 - External limit switch adjustment
- **Universal mounting plate**
 - Suitable for most common payloads
- **Corrosion resistant finish**
 - Black
- **Regenerative braking**
 - On motor shaft

POSITIONIT SPECIFICATIONS

Model	PI-35
Payload Capacity*	35 ft lb / 47 Nm
Height	9.7 in. / 246 mm
Width	10.8 in. / 273 mm
Depth	5.7 in. / 144 mm
Weight	19.5 lb / 8.9 kg
Operating Temperature	-20°C to 50°C / -4°F to 122°F
IP Rating	IP68 - Waterproof (immersion) and Dustproof
Pan Axis	400° (± 200°)
Pan Speed (proportional)	1° to 12° / second
Tilt Axis	180° (± 90°)
Tilt Speed (proportional)	1° to 12° / second
Backlash	≤ 0.15°
Repeatability	≤ 0.3°
Maximum Continuous Power	44 W
Maximum Running Current	1.85 amps
Input Voltage	24 VDC - Converters available for 12 VDC and AC power sources

*Capacity measured at 12 inches or less from the tilt axis. Dimensions and weights are for reference only and are subject to change. Contact Will-Burt for current engineering specifications.

POSITIONIT CONTROLLERS

The handheld and 2U rack mount controllers are Pelco-D compatible with programmable home and stow positions. The AC powered rack mount controller provides power and pan and tilt commands to the positioner and is adaptable to contact closure switches for I/O panels. The handheld controller has a keyboard for programming and an LCD screen and can be optionally used in conjunction with the rack mount controller.



CONTACT YOUR SALES REPRESENTATIVE TODAY

The Will-Burt Company, headquartered in Orrville, Ohio, USA, is the world's premier manufacturer of mobile telescoping masts, towers and pan and tilt positioners. We offer virtually every payload elevation and integration solution from the top brands; Will-Burt, GEROH, Integrated Tower Systems (ITS) and MAD – for defense, government, first responders, cellular, broadcast, energy production and other markets. Will-Burt also offers contract manufacturing, metal fabrication, powder-coating, and rapid prototyping services. All Will-Burt Company manufacturing locations are backed by a certified ISO 9001:2015 Quality Management System. Incorporated in 1918, Will-Burt is 100% employee-owned and is classified as a small business.



www.willburt.com

UNITED STATES WORLD HEADQUARTERS

401 Collins Blvd
Orrville, OH USA 44667
Telephone: 330.682.7015
Mast Customer Service: 330.684.4000
Fax: 330.684.1190
Email: info@willburt.com

INTEGRATED TOWER SYSTEMS

A WILL-BURT COMPANY

2703 Dawson Road, Tulsa, OK 74110
Telephone: 800.850.8535
Fax: 918.749.8537
Email: programs@itstowers.com

WILL-BURT EU

Unit 5b, Station Approach
Four Marks, Alton Hampshire,
GU34 5HN, United Kingdom
Telephone: +44 (0) 1403 265532
Fax: +44 (0) 1403 259072

WILL-BURT TURKEY

2118. Cad. No: 4, B101
Mustafa Kemal Mah. 06530 Çankaya
Ankara, Turkey
Telephone: +1 202 820 2184

EUROPE

GEROH

A Will-Burt Company
Fischergasse 25
91344 Waischenfeld, Germany
Telephone: +49-9202-18-0
Fax: +49-9202-18-11
Email: info@geroh.com

ASIA

SINGAPORE SALES OFFICE

1 Fullerton Road,
#02-01 One Fullerton,
Singapore 049213
Telephone: +65 6832 5689
Fax: +65 6722 0664