

POSITIONIT[®]

New Heavy-Duty Pan and Tilt Positioner by Will-Burt

- Payload Capacity – Up to 150 ft.-lbs. / 202 Nm
- Waterproof – IP 68 Rated
- Pelco-D Communications
- Universal Mounting Plate

PositionIt by Will-Burt is a maintenance-free pan and tilt positioner designed to provide years of trouble-free service. An IP68 rating delivers dust and water protection. The gear box is designed to minimize backlash and provides higher gear ratios for lower speeds along with mechanical braking. Long-life potentiometers are standard with PositionIt.

ESSENTIAL FEATURES

- **Replacement for MOOG QuickSet QPT Positioners**
 - Direct connection to existing QuickSet control/power cable
- **Pelco-D RS-485 Communications**
- **Strong lightweight construction**
 - Die-cast aluminum casing
- **Minimal backlash**
 - Precision turned and milled components with ball races on major axes
- **Built to last**
 - Stainless steel fasteners
- **Weatherproof**
 - IP 68 rating
- **Simple to install**
- **Universal mounting plate**
 - Suitable for most common payloads
- **Corrosion resistant finish**
 - Black
- **Regenerative braking**
 - On motor shaft
- **Long operational life**
 - 2 year warranty on Will-Burt PositionIt™ Positioners
 - 3 year mechanical and electrical warranty on Static Positioners
- **Flexible connection**
 - Bottom or side
- **We also offer a complete range of positioners for fixed applications and camera enclosures.**



POSITIONIT SPECIFICATIONS

Model	PI-150	PI-75
Payload Capacity*	150 ft lb / 202 Nm	75 ft lb / 101 Nm
Height	11.32 in. / 287.7 mm	11.32 in. / 287.7 mm
Width	12.4 in. / 314 mm	9.21 in. / 234 mm
Depth	6.8 in. / 171 mm	6.8 in. / 171 mm
Weight	37 lb / 16.8 kg	35 lb / 16 kg
Operating Temperature	-20°C to 50°C / -4°F to 122°F	
IP Rating	IP68 - Waterproof (immersion) and Dustproof	
Pan Axis	400° (± 200°)	
Pan Speed (proportional)	0.02 to 6.5° / second	
Tilt Axis	180° (± 90°)	
Tilt Speed (proportional)	0.02 to 5.5° / second	
Backlash	≤ 0.15°	
Repeatability	≤ 0.3°	
Maximum Continuous Power	44 W	
Maximum Running Current	1.85 amps	
Input Voltage	24 VDC - Converters available for 12 VDC and AC power sources	

*Capacity measured at 12 inches or less from the tilt axis. Dimensions and weights are for reference only and are subject to change. Contact Will-Burt for current engineering specifications.

POSITIONIT CONTROLLERS

The handheld and 2U rack mount controllers are Pelco-D compatible with programmable home and stow positions. The AC powered rack mount controller provides power and pan and tilt commands to the positioner and is adaptable to contact closure switches for I/O panels. The handheld controller has a keyboard for programming and an LCD screen and can be optionally used in conjunction with the rack mount controller.



CONTACT YOUR SALES REPRESENTATIVE TODAY

The Will-Burt Company, headquartered in Orrville, Ohio, USA, is the world's premier manufacturer of mobile telescoping masts, towers and pan and tilt positioners. We offer virtually every mobile payload elevation and integration solution for defense, government, first responders, cellular and mobile, broadcast, energy production and other markets. Will-Burt also offers contract manufacturing, metal fabrication, powder-coating, and rapid prototyping services. Will-Burt is an international company with offices and manufacturing in the USA, England, and Germany along with offices in Singapore and a joint venture in Turkey. All Will-Burt Company manufacturing locations are backed by a certified ISO 9001:2015 Quality Management System. Incorporated in 1918, Will-Burt is 100% employee-owned and is classified as a small business.



WILL-BURT NORTH AMERICA

WORLD HEADQUARTERS

401 Collins Blvd., Orrville, OH USA 44667
Telephone: +1 330 682 7015
Mast Customer Service: +1 330 684 4000
Fax: +1 330 684 1190
Email: info@willburt.com

WILL-BURT GERMANY

Fischergasse 25
D-91344 Waischenfeld
Germany
Telephone: +49 9202 180
Fax: +49 9202 1811
Email: info@willburt.com

WILL-BURT UNITED KINGDOM

Unit 5b, Station Approach
Four Marks, Alton Hampshire,
GU34 5HN, United Kingdom
Telephone: +44 (0) 1403 265532
Fax: +44 (0) 1403 259072
Email: info@willburt.com

WILL-BURT ASIA

SINGAPORE SALES OFFICE
1 Fullerton Road, #02-01 One Fullerton,
Singapore 049213
Telephone: +65 6832 5689
Fax: +65 6722 0664
Email: info@willburt.com

INTEGRATED TOWER SYSTEMS

A WILL-BURT COMPANY

2703 Dawson Road, Tulsa, OK 74110
Telephone: +1 800 850 8535
Fax: +1 918 749 8537
Email: programs@itstowers.com

WILL-BURT TURKEY

Ahi Evran OSB Mahallesi,
Nahcivan Caddesi, No: 8/2,
Sincan, Ankara 06935
Telephone: +1 202 820 2184
Email: HBeasey@willburt.com